

HAP IP66 2,1W

Segnapassi / Guide lights





KELVIN	CRI	LUMEN EFFETTIVI / REAL OUTPUT	CLASSE ENERGETICA / ENERGY CLASS
2700	90	~ 90	G
3000	90	~ 90	G
4000	80	~ 115	G

2006/95/CE -- 2002/95/CE -- 1907/2006/CE -- 2010/30/UE -- EN 60598-1 -- EN 60598-2-1
EN 60598-2-2 -- EN 62471 -- EN 62031



Hap IP66 2,1W



Foro: 33mm / Hole: 33mm

INCLUDED



Codice/Cod: **3435**

FORMA SHAPE	FINITURA FINISH	COLORE COLOUR	OTTICHE OPTICALS
Tondo / Round	Black	4000 K	Asymmetric
Quadrato / Square	■ SILK SCREENED	3000 K	
		2700 K	
		Red	
		Green	
		Blu	

ACCESSORI / ACCESSORIES

305000012	Controcassa / Outer casing
330010000	(Vin 220/240Vac) 700mA - 7.7W - IP20
330009700	(Vin 220/240Vac) 700mA - 10W - IP20
330009500	(Vin 220/240Vac) 700mA - 14W - IP67
330009900	(Vin 220/240Vac) 700mA - 30W (min 14W) - IP67
330007800	(Vin 220/240Vac) 700mA - 20W (min 7W)
330007200	(Vin 220/240Vac) 700mA - 28W (min 2W) - Dimmer Push, 0-10, 1-10, DALI
307500010	Cavo neoprene 2x0,5 / Neoprene cable 2x0.5
307500020	Connettore IP68 / IP68 connector

Descrizione / description

Faretti segnapasso a parete da incasso per esterni IP66 da 2.1W. Installazione con molle su contropareti in cartongesso o con controcassa su muratura. Disponibile con flangia tonda e quadrata. Flangia in vetro serigrafato nero, corpo in alluminio anodizzato nero. Disponibili nelle temperature colore 2700K - CRI90 / 3000K - CRI 90 / 4000K CRI80, MacAdam Step 3. Ottica asimmetrica. Fornito con 1m di cavo neoprene sezione 2x0.5mm². Durata L80 B20 a 100.000h Ta (temperatura ambiente) 25°. Alimentatore da ordinare separatamente.

IP66 2.1W recessed wall mounted steplights for outdoor use. Installation with springs on plasterboard false wall or with housing box for masonry. Available with round and square shape. Black silk screened glass flange and black anodized aluminium body. Colour temperatures 2700K - CRI90 / 3000K - CRI 90 / 4000K CRI80, MacAdam Step 3. Asymmetric optics. Supplied with 1m neoprene cable 2x0.5mm². Lifespan L80 B20 at 100,000h Ta (ambient temperature) 25°. Driver to be ordered separately.